



## Technical information

	F200300PA 201, 203, 270E, 303*	F400PA 402, 403, 450E*	F500600PA 501, 503, 550E, 601, 603, 650E*	FsensePAC Sense*
Dimensions	18 x 14 x 1.8 in. 454 x 365 x 45 mm	21 x 10 x 3.8 in. 521 x 250 x 95 mm	13 x 9 x 2.8 in. 330 x 235 x 69 mm	17.4 x 5.5 x 2.3 in. 442 x 140 x 58 mm
Weight	1.32 lbs 600 g	1.94 lbs 880 g	0.85 lbs 1 161** g	1.64 lbs 746 g
Filter type	Gradient structured filter with ultrasonically bonded polypropylene fibers free of chemicals and binders.*** Naturally anti-bacterial. Fiber shedding resistant.	Gradient structured filters with thermally bonded fibers containing polypropylene and polyethylene free of chemicals and binders.*** Naturally anti-bacterial. Fiber shedding resistant.		
				Extra filter sheets coated with activated carbon
Pleats:	73	92	156**	92**
Effective filter area:	31.2 ft <sup>2</sup> 2.9 m <sup>2</sup>	45.7 ft <sup>2</sup> 4.25 m <sup>2</sup>	49.5** ft <sup>2</sup> 4.59** m <sup>2</sup>	32.7** ft <sup>2</sup> 3.04** m <sup>2</sup>
Basis Weight:	1.66 lbs/ft <sup>2</sup> 100 g/m <sup>2</sup>	1.83 lbs/ft <sup>2</sup> 110 g/m <sup>2</sup>	1.83 lbs/ft <sup>2</sup> 110 g/m <sup>2</sup>	1.83 lbs/ft <sup>2</sup> 110 g/m <sup>2</sup>
Media thickness:	0.024 in. 0.60 mm	0.039 in. 0.99 mm	0.039 in. 0.99 mm	0.039 in. 0.99 mm
Pleat separators	Non hazardous, EVA based, VOC free, UV resistant			
HEPASilent® technology	Certified efficiency 99.97% for particles down to 0.1 microns such as dust, pollen, bacteria, virus, pet dander, mold spores and other airborne particles.			
Recommended filter exchange	6 months (4 380 hours) when used 24 h a day			

\* Filters suitable for these models.

\*\* Weight, pleats and effective filter area are projected on a complete filter pack, set of two or three filters.

\*\*\* Due to the 100% synthetic structure the media is resistant to moisture so that it won't promote any microbial growth.